



# Advanced Bash Scripting

Robert Barthel, SCC, KIT



# How to read the following slides

Abbreviation	Full meaning
<code>\$ command -opt value</code>	<code>\$</code> = <b>prompt</b> of the interactive shell The full prompt may look like: <code>user@machine:path \$</code> The <code>command</code> has been entered in the interactive shell session
<code>&lt;integer&gt;</code> <code>&lt;string&gt;</code>	<code>&lt;&gt;</code> = Placeholder for integer, string etc
<code>foo, bar</code>	Metasyntactic variables
<code>\${WORKSHOP}</code>	<code>/opt/bwhpc/common/workshops/2021-12-01</code>

## Sources of this slides?

- <https://tldp.org/HOWTO/Bash-Prog-Intro-HOWTO.html> (intro)
- <https://tldp.org/LDP/abs/html> (advanced)
- `$ man bash`

# Where to get the slides/exercises/reservation?

■ [https://indico.scc.kit.edu/e/bwhpc\\_course\\_2021-12-01](https://indico.scc.kit.edu/e/bwhpc_course_2021-12-01) or

bwUniCluster: /opt/bwhpc/common/workshops/2021-12-01

horeka:/software/all/workshops/2021-12-01

■ exercises

■ slides

■ Workshop reservation:  
single node:

```
sbatch -p wspar ...
```

■ multi node:

```
sbatch -p wspar ...
```

The screenshot shows a navigation menu on the left with options: Overview, Agenda, Registration, Contact, and courses@bwhpc.de. The main content area contains text about the Steinbuch Centre's high-performance computing workshop, including dates (Starts 21 Oct 2021, Ends 21 Oct 2021) and location (Europe/Berlin). At the bottom right, there are icons for 'exercises' and 'slides'.

# How to do exercises?

- Login to cluster & Generate workspace „bwhpc-course“

```
$ ws_allocate bwhpc-course 30
Info: creating workspace
/pfs/work7/workspace/scratch/ab1234-bwhpc-course
remaining extensions : 3
remaining time in days: 30
```

- Copy examples to your workspace

```
$ WORKSHOP=/opt/bwhpc/common/workshops/2021-12-01
$ cd $(ws_find bwhpc-course)
$ mkdir -v 2021-12-01; cd 2021-12-01
$ cp -vpr ${WORKSHOP}/exercises/01 ./
```

- Submit jobs from your workspace

```
$ cd $(ws_find bwhpc-course)/2021-12-01/01
$ sbatch <jobscript>
```

# Why (not) Bash?!

## ■ Great at:

- managing batch jobs
- managing external programs
- invoking entire UNIX command stack & many builtins


- Powerful scripting language
- Portable and version-stable
- Bash almost everywhere installed

## ■ Less useful when:

- Resource-intensive tasks (e.g. sorting, recursion, hashing)
- Heavy-duty math operations
- Extensive file operations
- Need for native support of multi-dimensional arrays

# Goal

- Be descriptive!
  - Comment your code
    - e.g. via headers sections of script and functions.
  - Decipherable names for variables and functions
- Organise and structure!
  - Break complex scripts into simpler blocks e.g. use functions
  - Use exit codes
  - Use standardized parameter flags for script invocation.



# Header & Line format

- Sha-Bang = '#!' (= activates interpreter directive)

→ at head of file = 1. line only!

```
#!/bin/bash
```

- Options: e.g. debugging shell):

```
#!/bin/bash -x
```

- #!/bin/sh → invokes default shell interpreter → mostly Bash

- If path of bash shell varies:

```
#!/usr/bin/env bash
```

- Line ends with no special character!

- But multiple statements in one line to be separated by:

```
;
```

Semicolon

```
$ echo hello; echo World; echo bye
```

- Group commands

- In current shell:

```
{ cmd1; cmd2; }
```

- In subshell:

```
(cmd1; cmd2)
```

# Bash Output

## ■ echo

a) trails every output with a „newline“

```
$ echo hello; echo World
hello
World
```

b) prevent newline:

```
$ echo -n hello; echo World
helloWorld
```

c) parsing „escape sequences“

```
$ echo -e "hello\nWorld"
hello
World
```

## ■ printf = „enhanced“ echo

- by default no „newline“ trailing
- formatted output

```
$ printf hello; printf World
helloWorld$
```

```
$ printf "%-9.9s: %03d\n" "Integer" "5"
Integer : 005
```



# Special bash characters (1)

Chars with meta-meaning

## # Comments

- at beginning
- at the end
- **exception:** escaping, quotes, substitution

```
# This line is not executed
```

```
echo 'something' # Comment starts here
```

## \ Escape = Quoting mechanism for single characters

```
echo \#
```

## ' Full Quotes = Preserves all special characters within

```
echo '#'
```

## " Partial Quotes = Preserves some of the special characters, but not `${var}`

```
var=42  
echo "\${var} = ${var}"; echo '\${var} = ${var}'
```

# Special bash characters (2)

Chars with meta-meaning

`$( )`

Command substitution

old version: `` `` (backticks) → do not use anymore

```
$ echo "today = $(date)"  
today = Wed Oct 11 02:03:40 CEST 2017
```

`( )`

Group commands in a subshell

```
$ (ls -l; date)
```

`(( ))`

Double-parentheses construct

→ arithmetic expansion and evaluation

```
$ echo $((1 + 3))  
4
```

\$ prefixing of `(( ))` to return the value it holds

`[ ]`

Test builtin (cf. slide 25)

or

Array element (cf. slide 12)

# Globbering

- = filename expansion  
→ recognices and expands „wildcards“
- but this is **not** a Regular Expression interpretation (for such use awk/sed)

## ■ wildcards:

\* = any multiple characters

? = any single character

[] = to list specific character

e.g. list all files starting with a or b

```
$ ls [a,b]*
```

^ = to negate the wildcard match

e.g. list all files not starting with a

```
$ ls [^a]*
```

# Variables (1)

## ■ Substitution:

- No spaces before and after '='
- **Brace protect your variables!**  
→ check difference:
- Values can be generated by commands

```
var1=abcdef
```

```
var2=01_${var1}_gh
```

vs

```
var3=01_${var1}_gh
```

```
var4=$(date)
```

```
$ echo ${var2}
```

```
01_abcdef_gh
```

```
$ echo ${var3}
```

```
01_
```

## ■ Bash variables are untyped

→ essentially strings,

→ depending on content arithmetics permitted

```
$ a=41; echo $((a+1))  
42
```

```
$ a=BB; echo $((a+1))  
1
```

→ string has an integer value of 0

## ■ declare/typeset (bash builtin)

- set variable to integer, readonly, **array** etc.

```
$ declare -r a=1  
$ let a+=1  
bash: a: readonly variable
```

```
$ declare -a arr=( '1 2' 3)  
$ echo ${arr[0]}  
1 2
```

← space is separator

## Variables (2)

- declare – *cont.*

- Arrays: e.g. store file content in array:

- a) 1 element per string

```
a=( $(< file) )
```

=

```
a=( $(cat file) )
```

- b) 1 element for whole file

```
a=( "$(< file)" )
```

- c) 1 element per line

```
while read -r line; do  
    a+=( "${line}" )  
done < file
```

- Usage only **without \$** prefix when **declare, assign, export, unset**

```
declare -i a=41  
export a  
echo ${a}  
unset a  
echo ${a}
```

# Manipulation of Variables (1)

Syntax	Does?	Examples
<code>\${#var}</code>	String length	<code>\$ A='abcdef_abcd'; echo \${#A}</code> 11
<code>\${var:pos:len}</code>	Substring extraction:	
	a) via Parameterisation	<code>\$ POS=3; echo \${A:\${POS}:2}</code> de
	b) Indexing from right	<code>\$ echo \${A:(-2)}</code> cd
<code>\${var#sstr}</code>	Strip shortest match of \$sstr from front of \$var	<code>\$ sstr=a*b; echo \${A#\${sstr}}</code> cdef_abcd
<code>\${var%sstr}</code>	Strip shortest match of \$sstr from back of \$var	<code>\$ sstr=c*d; echo \${A%\${sstr}}</code> abcdef_ab
<code>\${var/sstr/repl}</code>	Replace first match of \$sstr with \$repl	<code>\$ sstr=ab; rp=AB; echo \${A/\${sstr}/\${rp}}</code> ABcdef_abcd
<code>\${var//sstr/repl}</code>	Replace all matches of \$sstr with \$repl	<code>\$ echo \${A//\${sstr}/\${rp}}</code> ABcdef_ABcd
<code>\${var/#sstr/repl}</code>	If \$sstr matches front-end, replace by \$repl	<code>\$ sstr=a; rp=z_; echo \${A/#\${sstr}/\${rp}}</code> z_bcdef_abcd
<code>\${var/%sstr/repl}</code>	If \$sstr matches back-end, replace by \$repl	<code>\$ sstr=d; rp=_z; echo \${A/%\${sstr}/\${rp}}</code> abcdef_abc_z

# Manipulation of Arrays

Syntax	Does?	Examples
<code>\${#array[@]}</code>	Number of elements	<pre>\$ dt=( \$(date) ); echo \${#dt[@]} 6</pre>
<code>\${array[@]:p1:p2}</code>	Print elements from no. <b>p1</b> to <b>p2</b> :	<pre>\$ echo \${dt[@]:1:2} Feb 25</pre>
<code>\${array[@]#sstr}</code>	Strip shortest match of \$sstr from front of all elements of Array	<pre>\$sstr=W*d; echo \${dt[@]#\${sstr}} Feb 25 10:18:22 CET 2015</pre>

## ■ Adding elements to an array:

### a) at the end:

```
$ dt+=( "AD" )  
$ echo ${dt[@]}  
Wed Feb 25 17:18:22 CET 2015 AD
```

### b) in-between

```
$ dt=( ${dt[@]:0:2} ':-)' ${dt[@]:2} )  
$ echo ${dt[@]}  
Wed Feb 25 :-) 17:18:22 CET 2015
```

# Exercise 1: Variables and Arrays (5min)

- Write a bash script that:
  - Has a **variable** named **outputfile** which:
    - Is readonly and consists of 3 strings:
      1. Environment variable \$LOGNAME
      2. Arbitrary string of 4 characters generated in subshell via:  
`mktemp -u XXXX`
      3. First 2 characters of the current month (→ use „date“) using a bash array

Hint:

```
array=( $(date) )
```



# Exercise 1: Variables and Arrays - Solution

- Write a bash script that:
  - Has a **variable** named **outputfile** which:
    - Is **readonly** and consists of 3 strings:
      1. Environment variable **\$LOGNAME**
      2. **Arbitrary string** generate in subshell via: (use „mktemp -u XXXX“)
      3. **First 2 characters** of the **current month** (→ use „date“) using a bash array

```
#!/bin/bash
${WORKSHOP}/solutions/01/exercise_1.sh

# in case language is en_us.utf8, month is 2.element in "date"
array=$(date)
month=${array[1]:0:2}

declare -r outputfile="${LOGNAME}_$(mktemp -u XXXX)_${month}.log"
echo ${outputfile}

# Try changing output file
outputfile="new"
```

# Output & Input Redirection (1)

Syntax	Does?	Examples
<code>exe &gt; log</code>	Standard output ( <b>stdout</b> ) of application <code>exe</code> is (over)written to file <code>log</code>	<code>\$ date &gt; log; cat log</code>
<code>exe &gt;&gt; log</code>	Standard output ( <b>stdout</b> ) of application <code>exe</code> is append to file <code>log</code>	<code>\$ date &gt;&gt; log; cat log</code>
<code>exe 2&gt; err</code>	Standard output ( <b>stderr</b> ) of application <code>exe</code> is (over)written to file <code>err</code>	<code>\$ date 2&gt; err; cat err</code>
<code>exe 2&gt;&gt; log</code>	Standard output ( <b>stderr</b> ) of application <code>exe</code> is append to file <code>log</code>	<code>\$ date 2&gt;&gt; err; cat err</code>
<code>exe &gt;&gt; log 2&gt;&amp;1</code>	Redirects <b>stderr</b> to <b>stdout</b>	<code>\$ date &gt;&gt; log 2&gt;&amp;1</code>
<code>exe1   exe2</code>	Passes <b>stdout</b> of <code>exe1</code> to standard input ( <b>stdin</b> ) of <code>exe2</code> of next command	<i># Print stdout &amp; stderr to screen and then append both to file</i> <code>\$ date 2&gt;&amp;1   tee -a log</code>
<code>exe &lt; inp</code>	Accept <b>stdin</b> from file <code>inp</code>	<code>\$ wc -l &lt; file</code>

# Output & Input Redirection (2)

## ■ Take care of order when using redirecting

### ■ e.g:

```
(ls -yz; date) >> log 2>&1
```

- Stdout (date) redirected to file „log“
- Stderr (invalid option of ls) redirected to file pointed to by stdout

```
(ls -yz; date) 2>&1 >> log2
```

- Stderr (invalid option of ls) redirected to stdout (channel), but not written file
- Stdout (date) redirected to file

## ■ Suppressing stderr

```
ls -yz >> log 2>/dev/null
```

Usage? Keep variable empty when error occurs

- e.g. list of files with extension log

```
list_logs="$(ls *.log 2>/dev/null)"
```

- if no files with extension log exist, \$list\_logs is empty

## Output & Input Redirection (3)

- Redirection of „all“ output in shell script to one user file  
→ generalise = define variable

```
#!/bin/bash
log="blah.log"
err="blah.err"

echo "value 1" >> ${log} 2>> ${err}
command >> ${log} 2>> ${err}
```

→ or use exec

```
#!/bin/bash

exec > "blah.log" 2> "blah.err"

echo "value 1"
command
```

→ all stdout and stderr after 'exec' will be written to blah.log and blah.err resp.

# Output & Input Redirection (4)

## ■ Reading input e.g. file line by line

```
#!/bin/bash
declare -i i=1
while read -r line ; do
    echo "line ${i}: ${line}"
    let i+=1
done < 01_input_file
```

`${WORKSHOP}/exercises/01/01_read_input.sh`

## ■ Reading output of other commands line by line, e.g. „ls -l”

```
#!/bin/bash
declare -i i=1
while read -r line ; do
    echo "line ${i}: ${line}"
    let i+=1
done < <(ls -l *)
```

`${WORKSHOP}/exercises/01/02_read_input.sh`

### Process substitution:

a form of redirection;  
input/output of process = temp file

# Manipulation of Variables (2)

## ■ Example:

```
#!/bin/bash
${WORKSHOP}/exercises/01/03_var_manipulation.sh

## Purpose: Define automatic output names for executables

exe="03_binary.x"

## Assume: $exe contains extension .x or .exe etc
sstr=".*"          ## substitution string
log="${exe%${sstr}}.log"  ## replace extension with .log
err="${exe%${sstr}}.err"  ## replace extension with .err

## Define command: echo and run
echo "${exe} >> ${log} 2>> ${err}"
${exe} >> ${log} 2>> ${err}
```

# Expansion of Variables

Syntax	Does?	Examples
<code>\${var-<b>-\${def}</b>}</code>	If \$var not set, set value of \$def	<pre>\$ unset var; def=new; echo \${var-<b>-\${def}</b>}</pre> <code>new</code>
<code>\${var:-<b>-\${def}</b>}</code>	If \$var not set or <i>is empty</i> , set value of \$def	<pre>\$ var=''; def=new; echo \${var:-<b>-\${def}</b>}</pre> <code>new</code>
		<pre><b># Job Id for interactive and Slurm runs</b> jobID=\${SLURM_JOB_ID:-<b>-\${BASHPID}</b>}</pre>
<code>\${var:<b>?-\${err}</b>}</code>	If \$var not set or <i>is empty</i> , print \$err and abort script with exit status of 1	<pre>\$ var=''; err='ERROR - var not set' \$ echo \${var:<b>?-\${err}</b>}</pre> <code>bash: var: <b>ERROR - var not set</b></code>

# Exit & Exit Status

- Exit terminates a script
- Every command returns an exit status
  - successfull = 0
  - non-successfull > 0 (max 255)
- **\$?** = the exit status of last command executed (of a pipe)

```
ls -xy 2>/dev/null; echo $?  
2
```

- Special meanings (avoid in user-specified definitions):
  - 1 = Catchall for general errors
  - 2 = Misuse of shell builtins
  - 126 = Command invoked cannot execute (e.g. /dev/null)
  - 127 = "command not found"
  - 128 + n = Fatal error signal "n" (e.g. kill -9 of cmd in shell returns 137)



# (Conditional) Tests

```
if condition1 ; then
    do_if_cond1_true/0
elif condition2 ; then
    do_if_cond2_true/0
else
    do_the_default
fi
```

condition	Does?	Examples
(( ))	Arithmetic evaluation	<pre>\$ if (( 2 &gt; 0 )) ; then echo yes ; fi yes</pre>
[ ]	Part of (file) test builtin, arithmetic evaluation only with -gt, -ge, -eq, -lt, -le, -ne	<pre>\$ if [ 2 -gt 0 ] ; then echo yes ; fi yes \$ # existence of file \$ if [ -e "file" ] ; then echo yes ; fi</pre>
[[ ]]	Extended test builtin; allows usage of &&,   , <, >	<pre>\$ a=8; b=9 \$ if [[ \${a} &lt; \${b} ]]; then echo \$? ; fi 0</pre>

# Typical File Tests

■ (not) exists:

```
if [ ! -e "file" ] ; then echo "file does not exist" ; fi
```

■ file is not zero:

```
[ -s "file" ] && (echo "file greater than zero")
```

■ file is directory:

```
[ -d "file" ] && (echo "This is a directory")
```

■ readable:

```
[ -r "file" ]
```

■ writeable:

```
[ -w "file" ]
```

■ executable:

```
[ -x "file" ]
```

■ newer that file2:

```
[ "file" -nt "file2" ]
```

■ Pitfalls when using variables:

wrong:

```
$ unset file_var; if [ -e ${file_var} ] ; then echo "yes" ; fi  
yes
```

right:

```
$ unset file_var; if [ -e "${file_var}" ] ; then echo "yes" ; fi
```

# for Loops

```
for arg in list
do
    command
done
```

- Iterates command(s) until all arguments of *list* are passed
- *list* may contain globbing wildcards

## ■ Example 1

```
#!/bin/bash
## Example 1: Loop over generated integer sequence
counter=1
for i in {1..10} ; do
    echo "loop no. ${counter}: ${i}"
    let counter+=1
done
```

## ■ Example 2

```
## Example 2: Loop over space separated list of strings
list="file_1,file_2,file_3"
for x in ${list//,/ " "} ; do
    echo ${x}
done
```

# while Loops

```
while condition
do
    command
done
```

- Iterates command(s) as long as *condition* is **true** (or exit status 0)
- Allows indefinite loops

- Example

```
#!/bin/bash

## Purpose: Loop until max is reached
max=10
i=1
while (( ${max} >= ${i} )) ; do
    echo "${i}"
    let i+=1
done
```

# Positional parameters (1)

= Arguments passed to the script from the command line

Special variable	Meaning, notes
\$0	Name of script itself
\$1, \$2, \$3	First, second, and third argument
\${10}	10th argument, <b>but if not brace protected</b> : \$10 = \$1 + 0
\$#	Number of arguments
\$*	List of all arguments as one single string
@	List of all arguments, each argument separately quoted

## Example:

Show differences  
between

`$*` and `@`

```
echo "Number PPs: #{#}"
```

```
i=1
```

```
for PP in #{@} ; do
```

```
    printf "%3.3s.PP: %s\n" "${i}" "${PP}"
```

```
    let i+=1
```

```
done
```

```
i=1
```

```
for PP in #{*} ; do
```

```
    printf "%3.3s.PP: %s\n" "${i}" "${PP}"
```

```
    let i+=1
```

```
done
```

```
#{WORKSHOP}/exercises/01/04_special_var.sh
```

# Positional parameters (2)

= Arguments passed to the script from the command line

Special variable	Meaning, notes
\$0	Name of script itself
\$1, \$2, \$3	First, second, and third argument
\${10}	10th argument, but if not brace protected: \$10 = \$1 + 0
\$#	Number of arguments
\$*	List of all arguments as one single string
@	List of all arguments, each argument separately quoted

## Shifting positions:

**shift**

Drops \$1 → shifts \$2 to \$1 → \$3 to \$2 and so → \$# is reduced by 1

# Conditional evaluation - case

```
case variable in
    condition1)
        do_if_cond1_true/0
        ;;
    *)
        do_the_default
        ;;
esac
```

- analog to switch in C/C++
- **to simplify multiple if/then/else**
- each condition block ends with double semicolon
- If a condition tests true:
  - a) commands in that block are executed
  - b) case block terminates

```
#!/bin/bash #{WORKSHOP}/exercises/01/05_case.sh

## Purpose: Color output red or blue
e0="\033[0m"; eR="\033[31;1m"; eB="\033[34;1m"
case ${1} in
    red)
        echo -e "${eR}This line is red${e0}"
        ;;
    blue)
        echo -e "${eB}This line is blue${e0}"
        ;;
    *)
        echo -e "Line wo color" ;;
esac
```

## Exercise 2 (10-15 min)

- Write Script that processes options:

-h

-i <integer>

without shell build getopt combining „positional parameter“, „shift“, „tests“, „case“ and „while“

Template: `${WORKSHOP}/exercises/01/06_proc_input.sh`

→ Replace everything between ... and ... by code

```
#!/bin/bash

while ...test total num_positional parameter (PP) greater zero... ; do
  case "PP1" in
    ## script option: -h
    ...PP is option1...) ...echo something...
    ;;
    ...PP is option2...) ...echo PP2...
    ...do PP shift...
    ;;
  esac
  ...do PP shift...
done
```



# Exercise 1: Solution

## Processing Input without *getopts*

- Combining: Positional parameter + shift + tests + case + while

```
#!/bin/bash
## Purpose: Processing positional parameters

while (( ${#} > 0 )) ; do
    case "${1}" in

        ## script option: -h
        -h) echo "${1}: This option is for HELP" ;;

        ## script option: -i + argument
        -i) echo "${1}: This option contains the argument ${2}"
            shift ;;

        ## default
        *) echo "${1}: This is non-defined PP" ;;

    esac
    ## Shifting positional parameter one to the left: $1 <-- $2 <-- $3
    shift
done
```

`${WORKSHOP}/solutions/01/06_proc_input.sh`

# Lifetime of Variables (1)

- Script execution:

- assigned variables only known during runtime
- assigned variables not known in „worker“ scripts until „exported“
- Example:

```
#!/bin/bash
```

```
${WORKSHOP}/exercises/01/07_master_parse_var.sh  
${WORKSHOP}/exercises/01/08_worker_get_var.sh
```

```
## Purpose: Demonstrate parsing of assigned variables
```

```
var1="Non-exported value of var1"
```

```
export var2="Exported value of var2"
```

```
worker_sh="./08_worker_get_var.sh"
```

```
## check if $worker_sh is executable for user
```

```
echo "${0}: \${var1} = $var1"
```

```
echo "${0}: \${var2} = $var2"
```

```
if [ -x "${worker_sh}" ] ; then
```

```
    "${worker_sh}"
```

```
fi
```

- **But:** export of variables in script to interactive shell session only via:

```
$ source script.sh (compare ~/.bashrc)
```

## Lifetime of Variables (2)

### ■ Environmental variables

a) can be read in e.g. `my_workDIR=${PWD}`

b) during script changed, example:

```
...  
## Purpose: Demonstrating effects on environmental variables  
  
## Changing it during runtime  
export HOME="new_home_dir"  
echo "${0}: \${HOME} = \${HOME}"  
...
```

```
${WORKSHOP}/exercises/01/09_env_var.sh
```

```
$ echo ${HOME}; ./06_env_var.sh; echo ${HOME}  
/home/kitt/scc/ab1234  
./env_var.sh: ${HOME} = new_home_dir  
/home/kitt/scc/ab1234
```

# awk & sed: Command substitution

## ■ awk

- full-featured text processing language with a syntax reminiscent of C
- use for complicated arithmetics or text or *regular expression* processing

### ■ Examples:

a) logarithm of variable:

```
a=10; echo ${a} | awk '{print log($1)}'
```

b) **print first col. reformated:**

```
awk '{printf "%20.20s\n", $1}' file
```

- One-liners: <https://github.com/jweslley/dotfiles/blob/master/docs/awk1line.txt>

## ■ sed

- non-interactive stream editor
- use for deleting blank or commented lines etc

■ Example: **delete all blank lines of a file:**

```
sed '/^$/d' file
```

- One-liners: <http://sed.sourceforge.net/sed1line.txt>

# Functions (1)

```
function my_name ()  
{  
    commands  
}
```

- Stores a series of commands for *later* or *repetitive* execution
- Functions are called by writing the **name**
- Functions also process positional parameters
- Example:

```
#!/bin/bash  
  
## Purpose: Demonstrating features of functions  
## Add to printf command the date string  
function my_printf ()  
{  
    printf "${0}: $(date): ${@}"  
}  
  
my_printf "Hello World\n"
```

```
./10_fct.sh: Mon Oct 25 11:57:40 CEST 2021: Hello World
```

# Functions (2)

- **local** variables: values do not exist outside function, example:

```
#!/bin/bash
## Purpose: Demonstrating features of functions

var1="global value"

## Function: assign to global var1 temporarily a local value
function locally_mod_var ()
{
    local var1=${1}
    if [ -z "${var1}" ] ; then
        return 1
    fi
    echo "fct: local \${var1} = ${var1}"
    var1="new value in fct"
    echo "fct: local \${var1} = ${var1}"
}

echo "main: global \${var1} = ${var1}"
locally_mod_var "${var1}"
echo "main: global \${var1} = ${var1}"
```

`${WORKSHOP}/exercises/01/11_fct.sh`

- **return**: Terminates a function, optionally takes integer = „exit status of the function“, do not use „exit“ integers above 255 (cf. slide 24).

# Trap

- Catch abort signals, e.g.
    - SIGHUP = Hangup
    - SIGINT = Interrupt (Ctrl + C)
    - SIGTERM = Termination signal (kill -15)
- and do something (e.g. cleanup) before abort

- Example:

```
#!/bin/bash
```

```
${WORKSHOP}/exercises/01/12_trap.sh
```

```
cleanup(){  
    echo "Cleanup before interrupt and exit"  
    exit 0  
}  
  
## Trap interrupt with function cleanup  
trap "cleanup" SIGINT  
  
## Loop forever doing not really anything  
while true ; do  
    echo "sleep 10"; sleep 10  
done
```

Thank you for your attention!